

Dynaric

# Stainless Steel Strapping Machines

Fulfilling Packaging and Strapping Requirements in Harsh Environments such as the **Poultry, Meat, Seafood, and Agricultural Industries**



Dynaric, Inc.



*Certified Minority Owned Business*  
P: (800) 526-0827 | F: (757) 363-8016 | E: [order@dynaric.com](mailto:order@dynaric.com) | W: [www.dynaric.com](http://www.dynaric.com)

# Dynaric

## Stainless Steel Strapping Machines

- **Anti-jam feature** eliminates strap jams in unit\*
- Internal dispenser (except for the ST1SS); minimizes required floor space, keeps strap dry
- Available in 220 volts, 3-phase with optional 110 volt, single phase or 460 volt, 3-phase
- An **electronic control pad** allows the operator to easily adjust timer functions, heater temperature setting and seal time\*
- **Digital display** reflects the unit's operational status, including an error read-out for easy troubleshooting\*
- **Easy strap feeding** and adjustable external tension control and heat seal allows operators to strap packages in easy, efficient manner
- **Easily adjustable table height** for a variety of conveyor configurations
- **Energy saving feature**; motor automatically shuts down when machine is not in use
- **Mobile**; casters allow for the machine to be easily moved throughout your facility
- Available for use with 3/8" or 1/2" strapping

\* Not available on DF-207S Side Seal, Semi-Automatic Model

SPECIFICATIONS	DF207S	DF11S	DF11SA	DF11SC	DF11SCA	DF117S	DF117SA	ST1SS
Standard Arch Size <small>Other arch sizes are available</small>	N/A	27.6" W x 15.75" H	27.6" W x 15.75" H	27.6" W x 15.75" H	27.6" W x 15.75" H	27.6" W x 23.6" H	27.6" W x 15.75" H	23.6" W x 19.6" H
<b>Width</b>	39.4"	25.6"	25.6"	25.6"	25.6"	25.6"	46.65"	23.9"
<b>Length</b>	23.6"	44.7"*	44.7"*	44.7"*	44.7"*	65.8"*	63.4"	59.5"
<b>Height</b>	32.6"	53.0"*	53.0"*	53.0"*	53.0"*	52.6"*	49.5"	63.6"
<b>Table Height</b>	32.8" - 34.0"	31.3"	31.3"	31.3"	31.3"	26.3" - 28.7"	25.2" - 26.0"	52.8"
<b>Weight</b>	209 lbs.	407 lbs.*	440 lbs.*	407 lbs.*	440 lbs.*	506 lbs.*	771 lbs.*	825 lbs.
<b>Cycle Time</b>	2.0 sec.	1.6 sec.*	1.6 sec.*	1.6 sec.*	1.6 sec.*	1.6 sec.*	1.6 sec.*	1.6 sec.*
<b>Tension</b>	7 to 120 lbs.	15 to 260 lbs.	15 to 260 lbs.	15 to 260 lbs.	15 to 260 lbs.	15 to 260 lbs.	15 to 260 lbs.	0 to 73 lbs.
<b>Maximum Pkg. Size</b>	Depending on Arch Size							
<b>Minimum Pkg. Size</b>	3.9"H x 2.4"W	1.8"H x 3.1"W	1.8"H x 8.5"W	1.8"H x 3.1"W	1.8"H x 8.5"W	2.8"H x 5.9"W	1.2"H x 1.6"W	3.9"H x 3.9"W
<b>Seal Head Location</b>	Side	Bottom	Bottom	Bottom	Bottom	Side	Side	Bottom
<b>Cycle Start</b>								
Foot Switch		●		●		●		
Push Button		●	●	●	●	●	●	●
Photocell			●		●		●	●
Strap Insert	●							
<b>Table Conveyor</b>								
Gravity Rolls	●	●		●		●		
Power Belts			●		●		●	●
<b>Corrosion Resistance</b>								
Cabinet	●	●	●	●	●	●	●	●
Internal	●	●	●			●	●	●
Arch	●	●	●	●	●	●	●	●

\*Dependent upon arch size

Connect with us



Certified Minority Owned Business

P: (800) 526-0827 | F: (757) 363-8016 | E: order@dynaric.com | W: www.dynaric.com