Dynaric, Inc.

D3300CM

Bottom Seal Mini Arch Strapping Machine

Designed to strap small packages as well as irregularly shaped items

Trim Moldings, Wooden Dowels, PVC Pipe, Round Filters and Steel Rods



quality printed plastic strapping can be custom printed with your company logo, name, information or message. Printed strapping is an economical way to identify special products, display your company logo and information or even for product security and more.



Dynaric, Inc.

D3300CM



11.2" (285mm)

7.8" (198mm)







The D3300CM 'Mini Arch' is designed with a smaller more compact arch and sealing head, offering users the ability to strap smaller packages as well as irregularly shaped items that most other machines are unable to strap such as trim moldings, wooden dowels, PVC pipe, and round filters. Combined with flat stainless steel table tops (standard on every machine) and fully adjustable tension controls, the D3300CM allows for items to be strapped fast, efficiently, and without damage.

The D3300CM machine offers "Jam-Free" technology and the ability to strap products "Hands-Free" making these machines versatile enough for almost any application.

At A Glance_

- New, state-of-the-art innovative design, with rounded corners for personal protection
- Compact, lightweight assembly, for easy mobility throughout your facility
- Compact, low maintenance sealer head
- Internal strap dispenser minimizes required floor space
- Stainless steel tensioning roller
- Cycle time capable of a throughput of 55 straps per minute
- Loop kick-out feature eliminates strap jams
- Faster warm-up time reduces production delays
- Easily accessible strap feed unit for trouble free automatic strap feeding
- Open coil cabinet permits visibility of internal strap coil
- Automatic strap discharge mechanism removes any leftover strap when strap coil is finished and in case of a misfeed
- External adjustment of strap tension by the simple turn of a dial

	DIMOCM	
В		
A	35.4" (900mm) D	25.1" (638mm)

31.5" (800mm)

64.6" (1718mm)

В

Overall Length:		35.4" (900mm)
Overall Height:		64.6" (1718mm)
Table Height:		31.5" (800mm)
Weight:		308 lbs. (140 kg)
Sealing Method:		Heat Seal
Seal Head Location:		Bottom
Strap Size:		9mm - 12mm
Electrical Consumptio	n:	500 Watts
Cycle Time:		55 straps/min.
Cycle Initiation:		Palm switch, tabletop
		photocell, foot switch
		or optional foot bar
Tension:		Adjustable External
		Control, 3-70 kg
Max. Package Size:		Governed by arch size
Min. Package Size:	Flat =	W 2.55" X H 1.37"
-		

Round =



.78" in diameter