

Dynaric

Stainless Steel Strapping Machines

Fulfilling Packaging and Strapping Requirements in Harsh Environments such as the **Poultry, Meat, Seafood, and Agricultural Industries**



Dynaric, Inc.



Certified Minority Owned Business
P: (800) 526-0827 | F: (757) 363-8016 | E: order@dynaric.com | W: www.dynaric.com

Dynaric

Stainless Steel Strapping Machines

- **Anti-jam feature** eliminates strap jams in unit*
- Internal dispenser (except for the N3400SCA); minimizes required floor space, keeps strap dry
- Available in 220 volts, 3-phase with optional 110 volt, single phase or 460 volt, 3-phase**
- An **electronic control pad** allows the operator to easily adjust timer functions, heater temperature setting and seal time*
- **Digital display** reflects the unit's operational status, including an error read-out for easy troubleshooting*
- **Easy strap feeding** and adjustable external tension control and heat seal allows operators to strap packages in easy, efficient manner
- **Easily adjustable table height** for a variety of conveyor configurations
- **Energy saving feature**; motor automatically shuts down when machine is not in use
- **Mobile**; casters allow for the machine to be easily moved throughout your facility
- Available for use with 3/8" or 1/2" strapping

* Not available on DF-207S Side Seal, Semi-Automatic Model

** N3400SCA uses 110 volts standard

SPECIFICATIONS	DF207S	DF11S	DF11SA	DF11SC	DF11SCA	DF117S	DF117SA	N3400SCA
Standard Arch Size <small>Other arch sizes are available</small>	N/A	27.6" W x 15.75" H	27.6" W x 15.75" H	27.6" W x 15.75" H	27.6" W x 15.75" H	27.6" W x 23.6" H	27.6" W x 15.75" H	23.6" W x 23.6" H
Width	39.4"	25.6"	25.6"	25.6"	25.6"	25.6"	46.65"	23.9"
Length	23.6"	44.7"*	44.7"*	44.7"*	44.7"*	65.8"*	63.4"	47.2"
Height	32.6"	53.0"*	53.0"*	53.0"*	53.0"*	52.6"*	49.5"	60.6"- 69.6"
Table Height	32.8"-34.0"	31.3"	31.3"	31.3"	31.3"	26.3"-28.7"	25.2"-26.0"	30.6"- 39.6"
Weight	209 lbs.	407 lbs.*	440 lbs.*	407 lbs.*	440 lbs.*	506 lbs.*	771 lbs.*	639 lbs.
Cycle Time	2.0 sec.	1.6 sec.*	1.6 sec.*	1.6 sec.*	1.6 sec.*	1.6 sec.*	1.6 sec.*	1.7 sec.*
Tension	7-20 lbs.	15-260 lbs.	15-260 lbs.	15-260 lbs.	15-260 lbs.	15-260 lbs.	15-260 lbs.	
Maximum Pkg. Size	Depending on Arch Size							
Minimum Pkg. Size	3.9"Hx2.4"W	1.8"Hx3.1"W	1.8"Hx8.5"W	1.8"Hx3.1"W	1.8"Hx8.5"W	2.8"Hx5.9"W	1.2"Hx1.6"W	1.3"Hx3"W
Seal Head Location	Side	Bottom	Bottom	Bottom	Bottom	Side	Side	Bottom
Cycle Start								
Foot Switch		●		●		●		
Push Button		●	●	●	●	●	●	●
Photocell			●		●		●	●
Strap Insert	●							
Table Conveyor								
Gravity Rolls	●	●		●		●		
Power Belts			●		●		●	●
Corrosion Resistance								
Cabinet	●	●	●	●	●	●	●	●
Internal	●	●	●			●	●	
Arch	●	●	●	●	●	●	●	●

*Dependent upon arch size

Connect with us



Certified Minority Owned Business

P: (800) 526-0827 | F: (757) 363-8016 | E: order@dynaric.com | W: www.dynaric.com