

D325

Battery Powered Strapping Tool for Plastic Strap



The D325 is lighter and more portable than pneumatic tools, yet delivers the same seal joint efficiency.

Use this tool anywhere without being dependent on an air compressor or electrical outlet because of its 14.4 volt rechargeable battery. The D325 offers easy strap feeding, adjustable seal time, tension settings and thickness settings. The D325 is well suited for vertical and horizontal strapping applications and works well with polypropylene, polyester strapping.

Two 14.4 volt batteries are included with the D325 that will deliver approximately 250 polypropylene or 120 polyester cycles per charge. The battery recharges in 40 minutes and has a life expectancy of 3,000 charges.

Looking for an alternative to the use of costly steel and polyester strapping? Look no further than the combination of the new D325 and our UltraBand strapping. Designed to deliver the security and performance heavy duty requirements demand.

Battery charger and two batteries are included

Length: 13.2" (335mm)

Height: 5.3" (135mm)

Width: 6.5" (165mm)

Weight: 9.7 lbs. (4.4 kg.)

Specifications listed above are with the battery attached to the tool

Item Number	Model	Strap Type	Width	Gauge	Tension Force	Joint Strength
D325-58-26-41	D325-58-HD	PP, PET	5/8" (15mm)	.026"-.041"	787 lbs.	75%
D325-34-26-41	D325-34-HD	PP, PET	3/4" (18.5mm)	.026"-.041"	787 lbs.	75%



5740 Bayside Road, Virginia Beach, VA 23455

Phone: (800) 526-0827 Fax: (757) 363-8016

E-mail: gd@dynaric.com

Web address: www.dynaric.com