

ST-POLI LT/MT/HT

PNEUMATIC FRICTION WELD STRAPPING TOOL FOR PLASTIC STRAP



The pneumatically operated POLI series of friction weld tools are compact and easy to use. With three versions available for light, medium, or high tension, the POLI series can handle any load requirement.

The POLI tool is available for use with 1/2", 5/8", and 3/4" wide Ultraband, polypropylene, and polyester strapping. No matter what your strapping requirements are, the POLI series of tools will easily handle them.



- * ERGONOMIC HANDLE
- * WIDE TENSION RANGE
- * COMPACT AND LIGHTWEIGHT
- * BOSCH MOTOR
- * EASY STRAP FEEDING

TECHNICAL SPECIFICATIONS

Package size:	Minimum flat package size is 4" Optional round package base kit 20" (available for LT and MT only)
Strap Type:	Ultraband, polypropylene, and polyester
Strap Width:	L T: 3/8" to 3/4" MT -HT: 1/2" to 3/4"
Strap Thickness:	L T: 0.016" to 0.043" MT-HT: 0.024" to 0.050"

Max. Tension:	L T: 405 pounds MT: 580 pounds HT: 890 pounds
Air Pressure:	From 80 PSI to 94 PSI
Joint Type:	Friction Weld Seal
Weight:	Approx. 11.5 pounds

Dynaric, Inc.



®

5740 Bayside Road, Virginia Beach, VA 23455

Phone: (800) 526-0827 Fax: (757) 363-8016

E-mail: gd@dynaric.com

Web address: www.dynaric.com