

# DIGIT SMART HT

## Battery Powered Friction Weld Strapping Tool

Compact, easy to use and versatile for many strapping applications.

The Digit Smart tool incorporates a number of unique features to the tension and sealing areas that allow for precision operation. With minimal adjustments, the Digit Smart tool can be used with Ultraband, polypropylene, and polyester strapping from 5/8" up to 3/4" in width. To guarantee maximum performance right out of the box the strap type and size must be specified when ordering.



Control Pad

Included with the purchase of the tool you will receive two batteries and a charger.

## Specifications

Length:	13.7" (350mm)	Package Size:	Min. Flat Package is 4.7"
Width:	5.1" (130mm)		Min. Round Package Diameter is 27.5"
Height:	6.5" (165mm)	Strap Width:	5/8" (15mm) to 3/4" (19mm)
Strap Type:	Ultraband, PP and PET	Strap Thickness:	.031" (.8mm) to .050" (1.27mm)
Seal Type:	Friction Weld	Max. Tension:	Max. 765 lbs.
Weld Efficiency:	Up to 85%	Weight (w/Battery):	8.3 lbs.



5740 Bayside Road, Virginia Beach, VA 23455  
Phone: (800) 526-0827 Fax: (757) 363-8016  
E-mail: [gd@dynaric.com](mailto:gd@dynaric.com)  
Web address: [www.dynaric.com](http://www.dynaric.com)