



D3100A  
Fully Automatic  
Bottom Seal  
Strapping Machine

If you're looking for a fully automatic, operator-less strapping machine for your postal application, look no further than the newly designed D3100A / D3300A. This state-of-the-art unit offers lightweight construction, enhanced mobility, and a compact low maintenance sealing head and will strap and convey packages as small as 5 3/4" in width. With a cycle time of 1.2 seconds and a throughput of 50 straps per minute, depending on arch size, this unit will enhance any production line while cutting down on cost. The D3100A can be set to utilize 5mm and 6mm clear unembossed strapping. The D3100A uses 220V, three phase power (440V optional) and offers the user the opportunity to choose from manual strapping mode or automatic strapping mode (using two top mounted photo eyes) at the flick of an externally mounted switch.



PLASTIC STRAPPING SYSTEMS  
FOR THE POSTAL PACKAGING  
INDUSTRY



Dynaric exceeds the new USPS requirements with their line of "Postal Bundle" products. All Dynaric Postal Strapping has a clear smooth non-embossed surface with a haze factor below 20.



5740 Bayside Road, Virginia Beach, VA 23455  
Phone: (800) 526-0827  
Fax: (757) 363-8016  
E-mail: [gd@dynaric.com](mailto:gd@dynaric.com)  
Web address: [www.dynaric.com](http://www.dynaric.com)



DF30



## DF30

### Bottom Seal Semi Automatic Strapping Machine

The DF30 is an economical, easy to use strapping machine. Equipped with externally adjustable strap feed and electronic tension control, the DF30 is the perfect strapper for securing and unitizing outgoing shipments of mail trays or bundled mail. Additional safety for the operator, an audible cycle alert safety signal, "ACASS," is given when the strap has been inserted into the sealing mechanism prior to tensioning. The DF30 can easily be adjusted to use 5mm, 9mm, and 12mm strapping without additional parts.

D3100



## D3100

### Bottom Seal Automatic Strapping Machine

The newest generation of strapping machines from Dynaric, Inc. the D3100 is extremely well suited for use in the Mailing industry.

The D3100 is lightweight and mobile while continuing to offer a throughput of up to 50 straps per minute, depending on arch size. Faster warm up times, easy automatic strap loading and automatic strap misfeed discharge all help to decrease machine downtime. The D3100 can be set to utilize low cost 5mm and 6mm strapping. Using 120V single-phase power this unit can be used virtually anywhere. For easier mail tray maneuverability the D3100 offers fully stainless steel roller table tops.

D2400



## D2400

### Bottom Seal Automatic Strapping Machine

Commonly used in mailrooms, the D2400 strapper offers the latest technological innovations and operator features. It is capable of strapping 50 cycles per minute and features the industry's first ultrasonic bundle sensor for precise tension control on packages. The D2400 accommodates the user with its easy automatic strap feed function, automatic strap re-feed function, easy coil change and adjustable machine height. This machine uses 5mm, 6mm, and 9mm and can operate on 110V or 220V single-phase power. It can be operated by means of a footbar or a table top electric eye.

Unlike most competitive machines, the operating modes for both machines are foot pedal (D3100), foot bar (D2400), push button and electronic table top switch, and are all standard. This allows for much versatility in operating the equipment with operators feeding and strapping packages from both sides of the equipment.

